



ATOMIS

Inlite 170

Premium round recessed LED downlight with a glare-reducing reflector and satin diffuser (UGR < 19).

CATEGORY

Downlights & recessed spots

MOUNTING

Ceiling-mounted

IP CLASS

IP20 naar boven / IP40 naar beneden

COLOUR TEMPERATURE

**2700K / 3000K / 3500K / 4000K /
Tunable White**

CRI

CRI80 / CRI90 / CRI97

UGR

UGR <19

Introduction

Premium round recessed LED downlight with a glare-reducing reflector and satin diffuser (UGR < 19).

With the Inlite 170, you choose architectural lighting that unites design and light quality. Designed for hospitality, office, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	Ceiling-mounted
Application	Hospitality, Office, Education, Public spaces
Dimensions	Zaagmaat 150 mm
Material	Acrylic, Steel
Optics	Opal diffuser, Reflector
UGR	UGR <19
IP class	IP20 naar boven / IP40 naar beneden
CRI	CRI80 / CRI90 / CRI97
CCT	2700K / 3000K / 3500K / 4000K / Tunable White
Control	1-10V dimmable, Casambi dimmable, DALI dimmable, Optional
Emergency lighting	1-hour emergency power, Optional, Optional 1-hour autonomy self-test
Service life	L90B50 @ 60.000h, Tq 25°C
Voltage / freq.	220-240V, 50/60Hz
Efficiency	>125 lm/W
CIE flux code	93 100 100 100 100
Photobiological safety	IEC 62471: RG1, Low risk
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Colour	On request
Brand	Atomis
Category	Downlights & recessed spots

Product photos

Atmosphere and product images



Specification text

Atomis Inlite 170 recessed LED downlight. Round recessed LED downlight for ceiling mounting with a cut-out size of 150 mm, fitted with a glare-reducing reflector and a satin diffuser for a comfortable light image with UGR < 19. Built in insulation class II with a luminaire efficiency of more than 125 lm/W, photobiological safety in accordance with IEC 62471 RG1 (low risk) and an expected service life of L90B50 at 60,000 operating hours (Tq 25°C).

Information

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 3 July 2026